



NTN Bearing de Mexico, S.A.



7328 BCBM Bearing 2D drawings and 3D CAD models

140 mm x 300 mm x 62 mm SKF 7328 BCBM
Angular Contact Ball Bearings

Bearing No. 7328 BCBM

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	21.31
EAN	7316577746047
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	140MM Bore; 300MM Outside Diameter; 62MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap



NTN Bearing de Mexico, S.A.

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7328 BCBM
Weight / LBS	46.939
B	2.441 Inch 62 Millimeter
d	5.512 Inch 140 Millimeter
D	11.811 Inch 300 Millimeter
bore diameter:	140 mm
radial static load capacity:	345 kN
outside diameter:	300 mm
cage material:	Brass
overall width:	62 mm
outer ring width:	62 mm
contact angle:	40 °
maximum rpm:	2600 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	3 mm
radial dynamic load capacity:	302 kN
series:	73
d	140 mm



NTN Bearing de Mexico, S.A.

D	300 mm
B	62 mm
d ₁	202.5 mm
d ₂	172.15 mm
D ₁	242.55 mm
a	123 mm
r _{1,2} min.	4 mm
r _{3,4} min.	1.5 mm
d _a min.	158 mm
D _a max.	283 mm
D _b max.	291 mm
r _a max.	3 mm
r _b max.	1.5 mm
Basic dynamic load rating C	302 kN
Basic static load rating C ₀	345 kN
Fatigue load limit P _u	9.8 kN
Reference speed	2600 r/min
Limiting speed	3000 r/min
Calculation factor A	2.14
Calculation factor k _r	0.09
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y ₀	0.26
Calculation factor Y ₂	0.57
Calculation factor X	0.57
Calculation factor Y ₀	0.52
Calculation factor Y ₁	0.55
Calculation factor Y ₂	0.93
Mass bearing	21.5 kg