



# NTN Bearing de Mexico, S.A.



2218-K Bearing 2D drawings and 3D CAD models

## CONSOLIDATED BEARING 2218-K Self Aligning Ball Bearings

Bearing No. 2218-K

|                         |   |
|-------------------------|---|
| Category                | Self Aligning Ball Bearings   |
| Inventory               | 0.0   |
| Manufacturer Name       | CONSOLIDATED BEARING  |
| Minimum Buy Quantity    | N/A   |
| Weight                  | 3.33  |
| EAN                     | 0644075112291   |
| Product Group           | B00152  |
| Mounting Method         | Tapered Adapter   |
| Enclosure               | Open  |
| Rolling Element         | Ball Bearing  |
| Adapter Sleeve          | H-318   |
| Cage Material           | Steel   |
| Precision Class         | ABEC 1   ISO P0   |
| Internal Clearance      | C0-Medium   |
| Number of Rows of Balls | Double Row  |
| Other Features          | Allowable Misalignment 4 Deg   1:12 Taper   |
| Long Description        | 90MM Bore; Tapered Adapter Mount; 160MM Outside Diameter; 40MM Inner Race Width; 40MM Outer Race Width; Open; Steel Cage; Double Row of Balls; ABEC 1   ISO P0; C0-Medium |
| Inch - Metric           | Metric  |
| Category                | Self Aligning Ball Bearings   |
|                         |   |



## NTN Bearing de Mexico, S.A.

|                          |   |
|--------------------------|---|
| UNSPSC                   | 31171532  |
| Harmonized Tariff Code   | 8482.10.50.68   |
| Noun                     | Bearing   |
| Keyword String           | Self Aligning   |
| Manufacturer URL         | <a href="http://www.consbrgs.com">http://www.consbrgs.com</a> |
| Manufacturer Item Number | 2218-K  |
| Weight / LBS             | 7.341   |
| Outer Race Width         | 1.575 Inch   40 Millimeter                                    |
| Inner Race Width         | 1.575 Inch   40 Millimeter                                    |
| d                        | 3.543 Inch   90 Millimeter                                    |
| D                        | 6.299 Inch   160 Millimeter                                   |